

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 1999							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
Oregon Inlet							
600 27970	- Approach Lighted Whistle Buoy Ol		Mo (A) W		6	Red and white stripes.	Position frequently shifted with changing conditions. Topmark not installed on this aid.
							* 24/00
*6873	- Daybeacon 18				8	TR on pile.	
							24/00
6875	GREAT MACHIPONGO INLET NORTH CHANNEL JUNCTION LIGHT NC		Fl (2+1) R 6s	15	3	JR on pile.	
			*			*	24/00
23760	- CHANNEL LIGHT 12		Fl R 2.5s	13	3	TR on dolphin.	Light equipment removed from Dec. 1 to Mar. 15.
						*	* 24/00
Bivalve Channel							
24045	- LIGHT 1	38 18 42 N 75 53 48 W	Fl G 6s	15	4	SG on dolphin.	Light equipment removed from Dec. 1 to Mar. 15.
						*	* 24/00
27970 600	- Approach Lighted Whistle Buoy Ol		Mo (A) W		6	Red and white stripes.	Position frequently shifted with changing conditions. Topmark not installed on this aid.
							* 24/00

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 1999							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3200	- LIGHT 104		Q R	16	3	TR on pile.	
					*		24/00
10380 47500	COAST GUARD STATION BREAKWATER LIGHT	26 05 24 N 80 06 48 W	F R	9	3	On breakwater.	
	*						24/00
Dawho River							
34950	- Buoy 111	32 37 24 N 80 16 54 W				Green can with yellow square.	
		*					24/00
47500 10380	COAST GUARD STATION BREAKWATER LIGHT	26 05 24 N 80 06 48 W	F R	9	3	On breakwater.	
	*						24/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceeding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 1999							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
14995	- LIGHT 13	29 08 42 N 89 25 06 W	FI G 4s	17	3	SG on pile.	
		*					24/00
29045	- Buoy 14	29 42 12 N 84 58 30 W				Red nun with yellow triangle.	
		*					24/00
30015	- Buoy 37	30 17 30 N 85 51 18 W				Green can with yellow square.	
		*					24/00
CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 1999							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
688	NOAA Lighted Buoy 46029	46 07 00 N 124 30 36 W	FI (4) Y 20s			Yellow disk-shaped buoy.	
		*					24/00
3017	- RANGE REAR LIGHT 580 yards, 355° from front light.		Iso R 6s	56		KRW on pile.	Visible 1.5° each side of rangeline. Lighted throughout 24 hours.
	*						24/00
*3420	- Lighted Gong Buoy 10ES	33 55 13 N 118 26 30 W	Q R			Red.	Private aid.
							24/00
8665	- Buoy 5	42 25 30 N 124 25 18 W				Green can.	Maintained from May 15 to Oct. 10.
		*					24/00
8690	- ENTRANCE RANGE FRONT LIGHT	43 07 18 N 124 24 42 W	Q W	15		KRB on skeleton tower.	Visible 4° each side of rangeline.
	*						24/00
8695	- ENTRANCE RANGE REAR LIGHT 304 yards, 102° from front light.		Iso W 6s	30		KRB on skeleton tower.	Visible 4° each side of rangeline.
			*				24/00
9323	- LIGHT 20						Remove from list.
							* 24/00
10235	PILLAR ROCK LOWER RANGE FRONT LIGHT	46 15 12 N 123 32 36 W	Q W	20		KRB on pile structure.	Visible 4° each side of rangeline.
							* 24/00
15230	TOKE POINT JETTY LIGHT 3	46 42 24 N 123 58 00 W	FI G 4s	13	5	SG on piles.	Higher intensity beam down channel.
					*		24/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceeding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 1999							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
19350	Burrows Island Light	48 28 42 N 122 42 48 W	FI W 6s	57	W 10	White square tower on building. 34	HORN: 2 blasts ev 30s (2s bl-2s si-2s bl-24s si).
			*		*		* 24/00
23306.8	- Daybeacon 26	56 40 18 N 133 44 00 W				TR on pile.	
		*					24/00
*23306.8 3	- Daybeacon 26A	56 40 42 N 133 43 56 W				TR on pile.	
							24/00
29654	- HARBOR ENTRANCE CHANNEL LIGHT 4 75 feet outside channel limit.	21 19 06 N 158 07 06 W	FI R 4s	15	3	TR on pile.	
		*					24/00
CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
390	- LIGHT 68 Marks Weaver Shoal. (C)	44 55 54 N 74 04 06 W	Q R	45 14		White circular tower. 43	
							* 24/00
*Add Heading and Note: *Presque Isle Harbor Marina <i>*Lights and buoys maintained from May 15 to Oct 1.</i>							
11574	- Entrance Lighted Buoy 2	45 20 18 N 83 28 57 W	Q R			Red.	Private aid.
		*					* 24/00
11575	- Entrance Lighted Buoy 3	45 20 16 N 83 29 06 W	Q G			Green.	Private aid.
		*					24/00
*11595.5	- Entrance Buoy 8					Red nun.	Private aid.
							24/00
11600	- ENTRANCE LIGHT 10	45 20 24 N 83 29 09 W	FI R 2.5s	26 8		TR on post.	Private aid. HORN: 1 blast ev 20s (2s bl).
	*	*					* 24/00
11605	- ENTRANCE LIGHT 11	45 20 24 N 83 29 11 W	FI G 4s	26 8		SG on post.	Private aid.
	*	*					* 24/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceeding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
DULUTH - SUPERIOR HARBOR (Chart 14975)							
Superior Entry							
15595	- South Breakwater Light	46 42 37 N 92 00 22 W	FI G 5s	70 21	13	White cylindrical tower on fog signal building.	HORN: 1 blast ev 30s (3s bl). Operates from May 1 to Oct. 20.
		*					24/00
15600	- NORTH BREAKWATER LIGHT	46 42 41 N 92 00 30 W	Q R	38 12	5	TR on post.	
		*			*		24/00
15845	- South Breakwater Outer Light	46 46 49 N 92 05 15 W	F G	44 13	17	White tower on fog signal building. 35	HORN (2300-0700): 1 blast ev 60s for 2 min (4s bl-52s si), followed by 2 blasts (2s bl-1s si-5s bl-56s si). Operates from Apr. 1 to Dec. 1.
		*					* 24/00
15855	- North Pier Light	46 46 52 N 92 05 17 W	Iso R 6s	43 13	11	White cylindrical tower with black top and base. 37	
		*				*	24/00
*19040	SPRING LAKE OBSTUCTION LIGHT	43 04 24 N 86 12 50 W	FI W 2.5s	15 5	3	3 NW on pile worded DANGER.	
							24/00
CHICAGO HARBOR (Chart 14928)							
19930	THIRTY-FIRST STREET OUTER JETTY LIGHT	41 50 22 N 87 36 16 W	FI Y 2.5s	29 9		NW on cylindrical tower.	Maintained from Apr. 15 to Dec. 1. Private aid.
		*					24/00
19934	THIRTY-FIRST STREET INNER JETTY LIGHT	41 50 24 N 87 36 26 W	FI Y 2.5s	26 8		NW on cylindrical tower.	Maintained from Apr. 15 to Dec. 1. Private aid.
		*					24/00
Zion Intake							
<i>Lights maintained from Apr. 1 to Oct. 31.</i>							
20355	- Lighted Buoy A	42 26 37 N 87 47 25 W	FI W 2.5s			White can with orange bands and diamond.	Private aid.
		*					24/00
20360	- WEST LIGHT	42 26 39 N 87 47 32 W	Q W	5 2		NW on post.	Private aid.
		*					24/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceeding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
MILWAUKEE HARBOR (Chart 14924)							
Milwaukee							
20635	- Breakwater Light	43 01 37 N 87 52 55 W	FI R 10s	61 19	14	Black lantern on white square structure. 53	Structure is floodlighted from sunset to sunrise. Submarine cable runs to Milwaukee Pierhead Light. Illuminated sign on channelward side of light structure worded CABLE CROSSING NO ANCHORING. HORN: 2 blasts ev 20s (2s bl-2s si-2s bl-14s si). Operates from Apr. 1 to Nov. 1.
		*				*	* 24/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceeding the station number.